


# 2000mm Cold Water Soluble PVA Film

## **Basic Information**

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 10Rolls
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms: L/C, T/T
- Supply Ability:



### **Product Specification**

- Material:
- Working Temperature:
- Usage:
- High Light:
- Name:
- Highlight:

- Polyvinyl Alcohol(PVA)
- 170-180°C

China

Ciyu

FDA,SGS, TDS

US \$0.32-0.80/ Square Meter


Ciyu10001

Carton+Pallet

6,000 kgs per day

10-15days

- Packaging Film
  - Cold Water Soluble Film, Water Soluble Film
- Water Soluble Film
- ghlight:
- 2000mm Cold Water Soluble PVA Film, Artificial Marble PVA Film, 2000mm Water Soluble Film



### More Images



### **Product Description**

#### Water Soluble Plastic Wrap /Water Soluble Film

Clear Water Soluble Release Film In Artificial Marble / Helmets / Auto Silicone Tube

#### **PVA Film for Mold Releasing**

PVA film is an excellent option of mold releasing agent in unsaturated polyester epoxide resin or other thermosetting resin. Currently PVOH film has been widely used in the production of artificial marble, helmets, auto silicone tube and so on.

#### Advantage:

- a) From the performance, not easy to produce, after stripping blanks, save grinding time.b) With a high degree of softness and smoothness, PVOH film can make a more fitting mold, film of higher quality.
- c) Heat resistance: can heat up to 190 degree C.
- d) Good mechanical properties: tensile strength, elongation rate.
- e) Suitable for continuous production, high efficiency

#### Main specification and parameters

Category	parameter		Remark
Thickness	25µm~45µm		
Width	1000mm~2000mm		
Length	Regular standard: 1000m Max length: 1500m		Refer to products with 40µm thickness
Weight			Refer to products with 40µm thickness and 1200m length
Paper tube	3 inches		
<b>Transmittance</b>	80°~90°(%)		
Maxum temperature endurance	170ºC-180ºC		
Water soluble temperature	Normal	Under indoor Temperature	Solution rate is in proportion to
	Medium	Over 40ºC	water temperature.
	High	Over 80ºC	
Output	Delivery 7~10 days after ordered(normal standard and quantity)		



