

40Mu Solid Release High Temp PVA Water Soluble Film

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 10Rolls
- Price:

Our Product Introduction

- · Packaging Details:
- Delivery Time:
- Payment Terms: L/C, T/T
- Supply Ability:



Product Specification

- Material:
- Working Temperature:
- Usage:
- High Light:
- Thickness:

- Polyvinyl Alcohol(PVA)
- 170-180°C

China

Ciyu

FDA,SGS, TDS

US \$0.32-0.80/ Square Meter

Ciyu10001

Carton+Pallet

6,000 kgs per day

10-15days

- Release Film
- Cold Water Soluble Film, Water Soluble Film
- Highlight:
- 25-45microns
- 40Mu PVA Water Soluble Release Film, 40Mu PVA Release Film, 45 microns VA Water Soluble Film



More Images







Product Description

40Mu High Temp PVA Water Soluble Release Film Solid Material Release Application

PVA film is a new type of special function resin film material. The product is formed with water-soluble PVA as film substrate, adding auxiliary materials like plasticizer, soften agent, surface acting agent and dispersing agent, then finally finished thorough specific film-forming technology process.

Main Characteristics of PVA film products:

1. Water solubility. (Efficient water-soluble soft package material / Water-soluble liner film)

2. High barrier property. (Oxygen barrier; Antibacterial)

Main specification and parameters

| Category | parameter | | Remark |
|-----------------------------------|--|-----------------------------|--|
| Thickness | 25Mu~45Mu | | |
| Width | 1000mm~2000mm | | |
| Length | Regular standard: 1000m Max length: 1500m | | Refer to products with 40Mu thickness |
| Weight | Around 65kg per roll | | Refer to products with 40Mu thickness and 1200m length |
| Paper tube | 3 inches | | |
| Transmittance | 80°~90°(%) | | |
| Maxum temperature endurance | 170ºC-180ºC | | |
| Water soluble temperature | Normal Temp Type | Under indoor Temperature | Solution rate is in proportion to water temperature. |
| | Medium Temp Type | Over 40ºC | |
| | High Temp Type | Over 80ºC | |
| Output | Delivery 7~10 days after ordered(normal standard and quantity) | | |



